

Overview

Ez Glaze™ offers smart design, elegant glass-like appearance, versatility, low maintenance and sustainable performance.

Ez Glaze™ incorporates a proprietary profiled design which enables it to be installed over rafters & purlins with a high loading capacity.

Ez Glaze[™] is easy to fasten; the panels are simply screw fixed to the supportive structure and joined by overlapping.

Enjoy natural daylight and comfort with outstanding design and finish.

www.palram.com.au

Main Benefits


- Lightweight & easy to install
- Fits directly over rafters
- Clear and elegant glass appearance
- Hail & Impact resistant
- 99.9% UV Protection
- Minimal maintenance
- Extra durable

Typical Applications

- Pergolas and gazebos
- Patio enclosures
- Sunrooms
- Carports







Profile range

Profile	Rafter width	Profile height	Low profile height
EZ Glaze 50	40-50mm	39mm 36mm	22mm

Minimum roof pitch

Ensure that your roof pitch is at least 3 degrees. This will ensure adequate water run off.

Colour Range

Color	LT (%)	SC*	SHGC**
Clear	90	1.0	0.86
Grey	20	0.51	0.44
Breeze	70	0.61	0.53

^{*}Shading Coefficient

Additional colours are available subject to MOQ.

Loads Resistance

Wind Uplift: 2.0 Kpa Wind Load: 4.0 Kpa

Tested to comply with AS4040.1

Product Availability

Thickness	3 mm
Cover Width	600 mm
Total Width	673 mm
Maximum Length	7,000 mm

Flammability

EZ Glaze™ complies with the most demanding international fire resistance standards in the field of plastic.

 AS9705- Group 1 AS1530.3- Ignitability- 0, Spread of Flame-0, Heat Index- 0, Smoke- 2.

*For more detailed information please contact your Palram distributor.





PALRAM SA/NT

517A Cross Keys Road Cavan SA 5094 Tel: (08) 8262 2288 Fax: (08) 8262 3388 salessa@palram.com

PALRAM NSW/ACT

Unit 2, 26 Redfern St. Wetherill Park, NSW 2164 Tel: (02)8788 6100 Fax: (02) 8788 6199 salesnsw@palram.com

PALRAM QLD

Unit 9C / 380 Bilsen Road Geebung QLD 4034 Tel: (07) 3172 5581 Fax: (07) 3172 5516 salesqld@palram.com

PALRAM VIC/TAS

34 Buys Court Derrimut VIC 3030 Tel: (03) 9219 4444 Fax: (03) 9219 4455 salesvic@palram.com

PALRAM WA

74 Christable Way Landsdale WA 6065 Tel: (08) 9302 4173 Fax: (08) 9302 5287 saleswa@palram.com



In as much as Palram Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any Palram Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. Palram Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local Palram Industries supplier to ensure that you have obtained the most up to date information.



^{**}Solar Heat Gain (SHGC)

^{*} Maximum recommended single unit length is 7,000mm